

I-2

PATENT APPLICATION

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the Application of:

BRAY et al

Application No.: 10/776,314

Filed: February 12, 2004

For: DIGITAL DATA STORAGE AND ACCESS

**CLAIM FOR PRIORITY**

Director of the U.S. PTO  
P.O. Box 1450  
Alexandria, VA 22313-1450

January 6, 2005

Sir:

The benefit of the filing date of the following prior foreign application filed in the following foreign country is hereby requested for the above-identified patent application and the priority provided in 35 U.S.C. §119 is hereby claimed:

**United Kingdom Patent Application No. 0303110.1 filed on February 12, 2003**

In support of this claim, a certified copy of said original foreign application is filed herewith.

It is requested that the file of this application be marked to indicate that the requirements of 35 U.S.C. §119 have been fulfilled and that the Patent and Trademark Office kindly acknowledge receipt of this document.

Please charge any fee deficiency or credit any overpayment with respect to this paper to Deposit Account No. 01-2300.

Respectfully submitted,



Erik Cherdak  
Registration No. 39,936

1050 Connecticut Avenue, N.W.,  
Suite 400  
Washington, D.C. 20036-5339  
Tel: (202) 857-6000  
Fax: (202) 638-4810

EC:rkc

Enclosure: Priority Document (1)

THIS PAGE BLANK (USPTO)



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

## CERTIFIED COPY OF PRIORITY DOCUMENT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 3 February 2004

**THIS PAGE BLANK (USPTO)**

The Patent Office

THE PATENT OFFICE

12 FEB 2003

NEWPORT

1/77

12FEB03 E784213-6 D01063  
P01/7700 0.00-0303110.1

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP9 1RH**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference

RL.P52424GB

2. Patent application number

(The Patent Office will fill in this part)

0303110.1

12 FEB 2003

3. Full name, address and postcode of the or of each applicant (*underline all surnames*)Zarlink Semiconductor Limited  
Cheney Manor  
Swindon  
Wiltshire  
SN2 2QW

8177974001

Patents ADP number (*if you know it*)

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

4. Title of the invention

Digital Data Storage and Access

5. Name of your agent (*if you have one*)

Marks &amp; Clerk

"Address for service" in the United Kingdom to which all correspondence should be sent (*including the postcode*)4220 Nash Court  
Oxford Business Park South  
Oxford OX4 2RU  
United Kingdom

7271125001

Patents ADP number (*if you know it*)6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (*if you know it*) the or each application number

Country

Priority application number  
(*if you know it*)Date of filing  
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing  
(day / month / year)8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (*Answer 'Yes' if:*

Yes

- a) *any applicant named in part 3 is not an inventor, or*
  - b) *there is an inventor who is not named as an applicant, or*
  - c) *any named applicant is a corporate body.*
- See note (d))*

THIS PAGE BLANK (USPTO)

# Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.  
Do not count copies of the same document

Continuation sheets of this form

Description	8
Claim(s)	2
Abstract	1
Drawing(s)	3 1 3

10. If you are also filing any of the following, state how many against each item.

Priority documents	
Translations of priority documents	
Statement of inventorship and right to grant of a patent (Patents Form 7/77)	1
Request for preliminary examination and search (Patents Form 9/77)	1
Request for substantive examination (Patents Form 10/77)	
Any other documents (please specify)	

11. I/We request the grant of a patent on the basis of this application.

Signature *M. R. Lind* Date  
Marks & Clerk 11 February 2003

12. Name and daytime telephone number of person to contact in the United Kingdom Dr. Robert Lind  
01865-397900


## Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

## Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

THIS PAGE BLANK (USPTO)



The  
Patent  
Office

7/77

## Statement of inventorship and of right to grant of a patent

12 FEB 2003

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP9 1RH

1. Your reference RL.P52424GB

2. Patent application number  
(if you know it) **0303110.1**

3. Full name of the or of each applicant  
Zarlink Semiconductor Limited

4. Title of the invention  
Digital Data Storage and Access

5. State how the applicant(s) derived the right  
from the inventor(s) to be granted a patent  
By virtue of employment

6. How many, if any, additional Patents Forms  
7/77 are attached to this form?  
(see note (c))

7. I/We believe that the person(s) named over the page (and on  
any extra copies of this form) is/are the inventor(s) of the invention  
which the above patent application relates to.

Signature  
Marks & Clerk

Date  
11 February 2003

8. Name and daytime telephone number of  
person to contact in the United Kingdom Dr. Robert Lind  
01865-397900

### Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- d) When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- e) Once you have filled in the form you must remember to sign and date it.

**THIS PAGE BLANK (USPTO)**

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

Alvar BRAY  
28 Kewstoke Road  
Bristol  
BS9 1HB

856 399(001)

Patents ADP number (*if you know it*):

Marcus JONES  
55 Cranwell Street  
Lincoln

807 1474001

Patents ADP number (*if you know it*):

**Reminder**

**Have you signed the form?**

Patents ADP number (*if you know it*):

THIS PAGE BLANK (USPTO)

## DIGITAL DATA STORAGE AND ACCESS

The present invention relates to digital data storage and access and more particularly,  
5 though not necessarily, to a method and apparatus for storing digital video data and for  
accessing stored digital video data.

Traditionally, video data has been stored on video tape using video tape recorders. With  
the advent of digital television however, digital video storage devices making use of  
10 hard disk drives (HDDs) are being introduced. It can be expected that in the near future  
such storage devices will become commonplace in both the home and commercial  
environments. As well as being available as stand alone recording machines, storage  
devices using hard disk drives are likely to be integrated into digital set top boxes for  
receiving and decoding cable, satellite and terrestrial television signals, and into  
15 televisions themselves.

Digital video storage devices incorporating HDDs will make use of the latest computer  
related technologies. Indeed, it will be desirable to allow these devices to make use of  
current standard operating systems such as Linux and Microsoft Windows™ in order to  
20 simplify the development process, reduce costs, and provide open platforms (e.g. so that  
the devices can run third party applications). The chosen operating system will be able  
to make use of the same HDD which is used to store the digital video file system, to  
maintain the root file system storing for example MP3 files, drivers, applications, etc.

25 Standard operating systems such as Windows are designed to work satisfactorily with a  
range of hardware and software architectures. This tends to lead to a less than optimal  
performance on any given architecture. Consider a typical architecture in which a Hard  
Disk Drive Controller (HDDC) provides the interface for the computer system to the  
HDD. A Direct Memory Access (DMA) controller is responsible for the actual transfer  
30 of data between the HDDC and other system components via memory. The DMA  
handles these transfers in such a way that data does not need to pass through the  
microprocessor. The Hard Disk Drive Controller (HDDC), e.g. such as Integrated  
Drive Electronics (IDE), Enhanced IDE (EIDE), and Small Computer Systems Interface

(SCSI), can typically access the HDD within say 20mS. However, the operating system may introduce a significant overhead to this access time, resulting in a total access time in excess of 100mS. For this reason, the operating system is likely to operate side-by-side with a video system which will handle HDD access requests relating to the storage and retrieval of video data which will be stored in a partition of the HDD separate from that used by the operating system. The video system will be optimised for the particular architecture used, and the operating system and the video system will access the HDD via the same HDDC.

10 The inventors of the present invention have recognised that the sharing of the HDDC by the video and operating systems will require not only a modified video system design (as compared to the design which would be utilised were no operating system in use), but also a modified operating system. Both must be designed to allow some arbitration to take place over use of the shared HDDC. Arbitration is likely to make use of 15 semaphores, i.e. current status flags, which are maintained and accessed by code shared between the operating and video system software, to determine the status of the HDD and of requests being processed by the HDDC.

20 The need to modify standard software, such as for example Linux or Windows, is undesirable and in some cases impractical. The need for arbitration, including the repeated checking of the semaphores and/or the need to send interrupts from the DMA controller to the video or operating system, is also likely to add significantly to the 25 HDD access time. This is especially problematic for the video system where fast HDD access is an important requirement. Yet another disadvantage of this approach is that the video and operating systems will be less able to handle other tasks while a HDDC access request is being processed, given their active involvement in the arbitration process.

It is an object of the present invention to overcome or at least mitigate the disadvantages 30 noted in the preceding paragraph. This and other objects are achieved by the provision of pseudo HDDC register sets for each of the video and operating systems.

According to a first aspect of the present invention there is provided a device for storing and accessing digital data and comprising:

a hard disk drive partitioned to provide a separate file storage area for each of a plurality of applications or processing elements;

5 a Hard Disk Drive Controller for controlling access to the hard disk drive, the Hard Disk Drive Controller comprising at least one register for storing parameters defining a hard disk drive access operation and indicating the status of that operation;

at least two further registers corresponding in number to the number applications or processing elements, each further register arranged to store parameters defining a 10 hard disk drive access operation received from the associated application/processing element, and parameters indicating the status of that operation; and

processing means for exchanging parameters between the register of the Hard Disk Drive Controller and those of said two further registers.

15 The registers associated with the applications act as pseudo or proxy Hard Disk Drive Controller (HDDC) configuration registers, each providing a virtual memory access (e.g. DMA channel). This results in each of the video and operating system believing that it has sole use of the HDDC and hard disk drive. These systems therefore do not need to be modified over systems used in standalone architectures, and because the 20 systems are not involved in arbitration procedures to determine who can use the HDDC and when, hard disk drive access speeds are not as compromised as they would be if a software solution using semaphores were to be employed, since the "hardware" solution removes any interrupt latencies.

25 Preferably, said processing means and said further configuration registers are implemented using hardware.

Preferably, said processing means monitors read and write operations to the further registers, and arbitrates access to the Hard Disk Drive Controller.

30 Preferably, said processing means is arranged to facilitate hard disk drive access to each of said applications/processing elements in turn, transferring parameters identifying the data to be accessed from the further registers to the register of the Hard Disk Drive

Controller, and transferring status data from the Hard Disk Drive Controller registers to the further registers, and interrupts to the applications/processing elements.

In a preferred embodiment of the invention, the disk is partitioned to provide a storage  
5 area for a plurality of applications, the applications including at least an operating system and a video system, the latter making use of the hard disk to store digital video data. Preferably, the device includes one or more processing means for implementing said applications.

10 According to a second aspect of the present invention there is provided a method of accessing and storing digital data on a hard disk drive, the hard disk drive being partitioned to provide separate file storage areas for each of a plurality of applications/processing elements, the method comprising:

writing data defining disk access requests from said applications/processing  
15 elements to respective pseudo Hard Disk Drive Controller registers;

exchanging access request data and status data between the pseudo registers and a Hard Disk Drive Controller register such that at any given time the Hard Disk Drive Controller is actioning an access request from one of the applications/processing elements.

20 For a better understanding of the present invention and in order to show how the same may be carried into effect reference will now be made, by way of example, to the accompanying drawings, in which:

Figure 1 illustrates schematically a digital video storage device;  
25 Figure 2 illustrate schematically a part of the device of Figure 1; and  
Figure 3 is a flow diagram illustrating a method of operation of the device of Figure 1.

There is illustrated in Figure 1 a hardware architecture for a digital video storage device.  
This might be a stand alone unit or might form part of a larger system such as a set top  
30 box for receiving and decoding digital cable or satellite broadcasts. The device comprises a microprocessor 1 coupled to an address and data bus 2. The microprocessor runs an operating system such as Linux or Windows, and the video recording software which is typically a proprietary application written by or for the

manufacturer of the recorder. A memory 3 is also connected to the bus 2 and is used by the operating system. The memory also provides for buffering of transport streams, and video and audio data.

- 5 The other components of the recorder (coupled to the data and address bus 2 unless otherwise indicated) are:

MPEG De-multiplexer 4: This receives the transport stream from the tuner/demodulator and will filter the required video and audio MPEG streams into buffers in the memory.

- 10 The de-multiplexer also filters the system information tables that allow the Operating System software to display menus for choosing programs and channels to the user.

MPEG Video Decoder 5: This reads data from the video stream buffered in memory (from the de-multiplexer), and decodes the compressed data. The output from this

- 15 block 5 can then be fed to the display hardware.

MPEG Audio Decoder 6: This reads data from the audio stream buffered in memory (from the de-multiplexer), and decodes the compressed data. The output from this block can then be fed to the audio output hardware.

20

Hard Disk 7: This block contains the physical disk drive. On a top-end entertainment centre this could hold MP3 music files, video files, photographs, Internet cache and many other files. The operating system would therefore maintain a standard file system, such as FAT or EXT2FS, for the storage of non-video data and the video recording

- 25 software would have a separate partition to hold compressed video and audio stream data. The two would be separate since the performance of the standard OS file system is not typically sufficient to provide smooth video output in an embedded system. (In an embedded system the processor is not as powerful as in an average desktop PC)

- 30 DMA/IDE 8: This block provides the necessary hardware to initialise and communicate with the hard disk drive. When data is read or written to the disk the IDE hardware makes use of Direct Memory Access mechanisms to efficiently transfer data to and from the memory. The DMA/IDE may be integrated into a chip also providing other

components of the system, e.g. the microprocessor 1, or may be provided on a separate chip. The DMA/IDE is coupled to the hard disk 7 by a bus 9. Although the example described here makes use of IDE, it will be appreciated that the invention may be applied to systems using other drive interface standards including EIDE (Enhanced IDE) and SCSI (Small Computer Systems Interface).

The DMA channel enables the direct transfer of data between the hard disk 7 and other components of the recorder, i.e. the data does not need to pass through the microprocessor 1. This leaves the microprocessor free to perform other tasks once a data transfer has been initiated. The HDDC 8 comprises one or more hardware registers which in use store:

10      Status bit(s);  
              at least one status bit is set to indicate whether the IDE is active or inactive,

15      Configuration bits;  
              for hard disk access operation in progress, these bits identify the source and destination addresses and the block size for the data transfer,

20      The DMA 8 provides an interrupt IRQ which is intended for the microprocessor and which indicates when a disk access operation has been completed. This interrupt is generated by the DMA channel when an IDE access operation has been completed.

A new hardware block 10 is coupled to the data and address bus 2, between that bus and the IDE 8. The internal architecture of this block 10 is shown in more detail in Figure 2, and comprises a pair of identical "pseudo" registers 12,13 coupled to the bus 2.  
25      These registers have different addresses, with the operating system run by the microprocessor being "programmed" with a first address which identifies a first of the pseudo registers 12, and the video system being programmed with a second address which identifies the other pseudo register 13. In the video and operating systems, these addresses replace the IDE register address which would be used in conventional  
30      systems. The file and operating systems are unaware of the "re-direction" of their requests, and that they do not have direct access to the register of the IDE 8 (this register is shown in Figure 3, identified by the reference numeral 14). The bits of each of the pseudo registers 12,13 are mapped to the bits of the register 14 of the IDE, such that

each pseudo-register provides a set of pseudo status bits and a set of pseudo configuration bits.

A controller 15 is responsible for the transfer of data between the pseudo registers 12,13  
5 and the IDE register 14. Another function of the controller 15 is to route IRQ interrupts from the DMA to the operating system or the video system depending upon whether a completed operation related to an operating system or video system access request. Consider the case where the operating system wishes to read from or write to the hard disk 7. Assuming that the operating system has received an IRQ indicating that the  
10 previous access request of the operating system has been completed, the operating system will write the necessary information, i.e. source and destination address and block size, to the configuration bits of the pseudo register 12.

The controller 15 polls the pseudo register 12 at regular intervals to determine if the  
15 virtual DMA channel has been enabled. If the controller 15 determines that this is the case, it then changes the status bit of the pseudo register 12 to indicate that the virtual DMA channel is active. The controller then checks the corresponding status bit of the IDE register 14. In the event that this indicates that the real DMA channel is inactive, the configuration bits of the first pseudo register 12 are loaded into the corresponding  
20 configuration bits of the IDE register 14. The status bit of the IDE register will be changed to indicate a DMA channel status of active, and the instruction processed by the IDE 16. When the DMA operation is complete, the status bit of the IDE register 14 will be changed to indicate the new status, and an IRQ passed to the controller 15 causing the controller to map this status bit to the status bit of the first pseudo register,  
25 indicating that the disk access operation is complete. The controller will also redirect the IRQ to the operating system. The operating system can then take the next access request from the stack of pending requests, and the process is repeated. The operation of the video system corresponds to that of the operating system vis-à-vis disk access, using the second pseudo register 13 rather than the first register 12.

30 Consider now the case where a disk access request is written to one of the pseudo registers 12,13, the controller changes the status bit of that register to indicate that the corresponding virtual DMA channel is active, and the controller then determines from a

polling of the appropriate status bit of the IDE register that the DMA is active (e.g. an access request is made by the operating system whilst an access request for the video system is being actioned). In this case, the controller will not yet transfer the configuration bits from the pseudo register to the IDE register. Rather, it will continue  
5 to poll the status bit of the IDE register until that bit indicates that the current access request is completed and the IDE inactive. At that time, the configuration bits will be transferred from the pseudo register to the IDE register.

In order to ensure equal access to the hard disk drive by both the operating and video  
10 systems, the controller 15 will transfer requests from the pseudo registers in turn (i.e. on a round-robin basis), unless of course one of the systems does not have a pending access requests in which case the controller may accept a series of requests from the other of the systems without interruption. In some implementations, one of the operating or video system may be given priority over the other system, to ensure a higher data  
15 throughput for the system with the higher priority.

It will be appreciated by the person of skill in the art that various modifications may be made to the above described embodiment without departing from the scope of the present invention. For example, whilst the embodiment described above is concerned  
20 with allowing an operating system and a video system to share access to a single hard disk drive, the invention can be applied to other applications requiring such access. The number of applications involved need not be limited to two – the number of pseudo registers would correspond to the number of applications. The invention could also be applied to a plurality of processors sharing access to a common hard disk drive.

**CLAIMS:**

1. A device for storing and accessing digital data and comprising:
  - a hard disk drive partitioned to provide a separate file storage area for each of a plurality of applications or processing elements;
  - 5 a Hard Disk Drive Controller for controlling access to the hard disk drive, the Hard Disk Drive Controller comprising at least one register for storing parameters defining a hard disk drive access operation and indicating the status of that operation;
  - at least two further registers corresponding in number to the number applications 10 or processing elements, each further register arranged to store parameters defining a hard disk drive access operation received from the associated application/processing element, and parameters indicating the status of that operation; and
  - processing means for exchanging parameters between the register of the Hard Disk Drive Controller and those of said two further registers.
- 15 2. A device according to claim 1, wherein said processing means and said further configuration registers are implemented using hardware.
3. A device according to claim 1 or 2, wherein said processing means monitors 20 read and write operations to the further registers, and arbitrates access to the Hard Disk Drive Controller.
4. A device according to any one of the preceding claims, wherein said processing means is arranged to facilitate hard disk drive access to each of said 25 applications/processing elements in turn, transferring parameters identifying the data to be accessed from the further registers to the register of the Hard Disk Drive Controller, and transferring status data from the Hard Disk Drive Controller registers to the further registers, and interrupts to the applications/processing elements.
- 30 5. A device according to any one of the preceding claims, the disk being partitioned to provide a storage area for a plurality of applications, the applications including at least an operating system and a video system, the latter making use of the hard disk to store digital video data.

6. A device according to claim 5 and comprising one or more processing means for implementing said applications.
- 5 7. A method of accessing and storing digital data on a hard disk drive, the hard disk drive being partitioned to provide separate file storage areas for each of a plurality of applications/processing elements, the method comprising:
  - writing data defining disk access requests from said applications/processing elements to respective pseudo Hard Disk Drive Controller registers;
- 10 exchanging access request data and status data between the pseudo registers and a Hard Disk Drive Controller register such that at any given time the Hard Disk Drive Controller is actioning an access request from one of the applications/processing elements.

**ABSTRACT**  
**DIGITAL VIDEO**

A device for storing and accessing digital video data comprises first processing means 1  
5 for implementing an operating system and a video system. A hard disk drive 7 is  
partitioned to provide a video file system storage area and an operating system file  
system storage area. A Hard Disk Drive Controller 8 controls access to the hard disk  
drive 7, the Hard Disk Drive Controller 8 comprising at least one register 14 for storing  
parameters defining a hard disk drive access operation and indicating the status of that  
10 operation. Two further registers 12,13 are associated with the video system and the  
operating system respectively, each further register being arranged to store parameters  
defining a hard disk drive access operation received from the associated system, and  
parameters indicating the status of that operation. Second processing means exchanges  
parameters between the register 14 of the Hard Disk Drive Controller 8 and those of  
15 said two further registers 12,13.

Figure 1

THIS PAGE BLANK (USPTO)

ARENT FOX PLLC  
1050 Connecticut Avenue, N.W., Suite 400  
Washington, D.C. 20036-5339  
Docket No. 108347-00018  
Serial No.: 10/776,314 Filed: February 12, 2004  
Inventor: BRAY et al




Figure 1

THIS PAGE BLANK (USPTO)

AREN'T FOX PLLC  
1050 Connecticut Avenue, N.W., Suite 400  
Washington, D.C. 20036-5339  
Docket No. 108347-00018  
Serial No.: 10/776,314 Filed: February 12, 2004  
Inventor: BRAY et al




Figure 2

THIS PAGE BLANK (USPTO)





Figure 3

THIS PAGE BLANK (USPTO)



ARENT FOX PLLC  
1050 Connecticut Avenue, N.W., Suite 400  
Washington, D.C. 20036-5339  
Docket No. 108347-00018  
Serial No.: 10/776,314 Filed: February 12, 2004  
Inventor: BRAY et al